



1K PLASTIC PRIMER

GENERAL

| CODE | DESCRIPTION |
|------|----------------------|
| PP10 | 1K plastic primer 1L |



DESCRIPTION

One-component colourless primer for application by brush or spray gun on car body parts made of plastic. In Car Refinish used as a primer coating and forming micro coating to obtain good adhesion topcoat to plastic.

APPLICATION

Store in tightly closed containers, in a cool, dry place away from sources of fire and heat. Avoid exposure to sunlight.



Number of layers: 2
Pressure: 2 - 2,5 bar
Nozzle: 1.3 - 1.4 mm



Flash off between layers: 20 min

DRYING TIMES



Operating hardness: 30-40 min at 20°C

After 30-40 min since applying the last layer of primer plastic, can be applied every type of topcoat.

PHYSICOCHEMICAL PROPERTIES

The maximum content of VOC for ready to use product is: < 840 g/l.

POIDS SPÉCIFIQUE

About 0.9 g/cm³



1K PLASTIC PRIMER

STORAGE

Store the product tightly closed in the original container, in dry and well ventilated place, away from fire and heat sources at the temperature from 5°C to 20°C. Do not expose to direct sunlight.

SHELF LIFE

Expiration date: 12 months from date of manufacture - date on the top of container.

HEALTH AND SAFETY RECOMMENDATIONS

Safety Data Sheet and the applicable regulations for health and safety at work involving exposure to chemical factors.

EQUIPMENT CLEANING

For cleaning equipment can be used acryl thinner or nitro thinner. It is recommended to use thinner for cleaning paint spray guns.