



CLEAR COAT 1K

GENERAL

CODE	DESCRIPTION
AS300	Clear coat 1K 500ml



DESCRIPTION

Clear Coat 1K is a high performance 1K lacquer which gives a crystal clear finish that can be applied over all water and solvent based basecoats. The surface gets a protective layer and a completely new look. Ideal for smart repairs.

PROPERTIES

- Ultra gloss finish with excellent gloss retention
- Superior build
- Ideal distance to object is 25 cm
- Apply 2 full layers with a flash-off time of 10 min for a good result
- UV and petrol resistant 1K lacquer
- Fast drying 1K lacquer

DIRECTIONS BEFORE USE

- Use at room temperature
- Shake before use
- Surface must be dry and clean, free from dirt, rust, grease etc.
- Spray crosswise thin layers on the object or surface to be coated
- Leave to evaporate/dry
- After use, to clean the nozzle and prevent blockage: hold the can up side down and spray until only gas is released

WORKING CONDITIONS

- Air temperature 15°C - 30°C
- Surface temperature 15°C - 30°C but above the condensation point
- Temperature of the can 18°C - 25°C
- Relative humidity: max 80%

DRYING TIMES

Depends on layer thickness, temperature and ventilation. Indication: dust dry ca. 15 min. Tack free ca 30 min. Dry ca. 2 hours.

STORAGE

Cool (10°C - 20°C) and dry