



## HIGH GLOSS BLACK

### GENERAL

#### CODE

AS080

#### DESCRIPTION

High gloss black 500ml



### DESCRIPTION

Gerko high gloss black is a decorative paint for any type of bodywork. Suitable for the individual decoration of cars and motorcycles. Ideal as contrast paint and for partial paintwork.

### PROPERTIES

- Fast drying
- Excellent adhesion on many surfaces and materials
- Exceptional hiding power
- Smooth finish
- Resistant to chemicals and weather conditions

### DIRECTIONS BEFORE USE

- Use on room temperature
- Shake thoroughly before use; at least 2 min after the shaking ball has come loose
- Surface must be dry and clean, free from dirt, rust, grease etc.
- When sprayed on bare metals or plastics a suitable primer is advisable
- Spray thin crosswise layers on the object or surface to be coated
- Leave to evaporate/dry
- After use, to clean the nozzle and prevent blockage: hold the can up side down and spray until only gas is released

### DRYING TIMES

Depends on layer thickness, temperature and ventilation. Indication: dust dry ca. 20 min. Dry to touch 40 min. Over paintable: after 60 min.

### WORKING CONDITIONS

- Air temperature 15°C - 30°C
- Surface temperature 15°C - 30°C but above the condensation point
- Temperature of the can 18°C - 25°C
- Relative humidity: max 80%

### APPLICATION TEMPERATURE, °C

- 15 - 30

### STORAGE CONDITIONS

Cool (10°C - 20°C) and dry

### SAFETY

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Pressurized container: do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid breathing spray. Wear protective gloves/ eye protection. Use only outdoors or in a well-ventilated area.