

TDS TECHNICAL DATA SHEET

WHEEL SPRAY

GENERAL

CODE	DESCRIPTION
AS130	Wheel spray light grey 500ml



DESCRIPTION

Gerko Wheel Spray is a glossy silver coloured spray paint perfect to repair rims very fast and easy.

PROPERTIES

- Very fast drying, good adhesion
- Glossy, good flexibility, good hardness
- Excellent UV protection
- Good outdoor durability
- Non yellowing

DIRECTIONS BEFORE USE

- Make sure that the surface is dry clean and free of oil, grease ect. Preferably the surface should be sanded lightly
- Spray with a distance of about 15 cm, cross wise, several layers until a smooth surface is formed
- Let it dry
- · Sand the layer lightly for the best adhesion of the next layer

DRYING TIMES

Depends on layer thickness, temperature and ventilation. Indication: dust dry ca. 30 min. Sandable ca. 5 hours. Overpaintable (with same product) after ca. 30 min.

WORKING CONDITIONS

- Air temperature 15°C 30°C
- Surface temperature 15°C 30°C but above the condensation point
- Temperature of the can 18°C 25°C
- Relative humidity: max 80%

RECOMMENDATIONS

- When used in combination with (unknown) primers, the compatibility and adhesion should be tested first
- For safety, health and to promote the drying, this product should only be use in well ventilated areas

SAFETY

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Pressurized container: do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid breathing spray. Wear protective gloves/ eye protection. Use only outdoors or in a well-ventilated area.

PAGE 1 | WHEEL SPRAY