



SUPERIOR MASKING FILM MOISTURE ABSORPTION

GENERAL

CODE	DÉSCRIPTION
SPM40	Superior masking film moisture absorption 4m x 150m
SPM50	Superior masking film moisture absorption 5m x 120m



DESCRIPTION

The Gerko blue transparent masking film has a special layer on the inside that absorbs any moisture residues on the car, so it can be applied to damp surfaces and prevents 'false spots'. This masking film is made extra thick, making it even stronger.

SPECIFICATION

- Corona treated for optimal adhesion of paint and overspray
- Special addition that ensures moisture absorption, in addition to the breathable functionality
- Foil thickness: 15 microns
- Easy to apply by one person
- Strong and elastic performance
- Easy to cut
- Statically charged, causing the film to be attracted to the surface
- Packed per roll in a carton box
- Can be used with infrared drying
- Temperature resistant up to 120°C
- Gerko logo on spray side

PRODUCT INFORMATION

FORM	MATERIAL	ROLL WIDTH	TEMPERATURE RESISTANCE	WATER SOLUBLE
Film on a roll	HDPE	95cm	120°C	No

TECHNICAL PROPERTIES

- Paint adhesive
- High static power
- High tensile strength
- IR drying by max 120°C
- Breathable
- Moisture absorbent



MASKING FILM MOISTURE ABSORPTION

STORAGE

+ 20°C/± 10°C, in an enclosed space with a relative humidity of 30-90% without exposure to UV

SHELF LIFE

12 months from delivery date