



SUPERIOR PRIMER

GENERAL

| CODE | DESCRIPTION |
|--------|-----------------------------------|
| SAS010 | Superior primer light grey 500 ml |
| SAS030 | Superior primer dark grey 500 ml |
| SAS040 | Superior primer white 500 ml |



DESCRIPTION

Gerko superior primer is a fast-drying, durable elastic primer with a very good filling and a perfect adhesion to various substrates like plastic, metal, old coating films, etc. It is designed to be used in higher layer thickness than “normal” primers. Gerko superior primer provides a completely smooth spray pattern, dries quickly, and is repaintable with all paint systems.

PROPERTIES

- High build primer
- Fast drying hard and flexible primer
- Excellent adhesion
- Easy sandability
- Anticorrosion properties to the use of zinc phosphate
- Can be applied straight on bare metals
- Petrol resistant
- Can be over painted with most modern paints
- Can be applied on almost all plastics

DRYING TIMES

Depends on layer thickness, temperature and ventilation. Indication: dust dry ca. 10 min. Over paintable after ca. 2 hours. Sandable ca. 15 min.

DIRECTIONS BEFORE USE

- Use on room temperature
- Shake before use
- Surface must be dry and clean, free from dirt, rust, grease etc.
- Spray cross wise layers, until sufficient layer thickness is achieved
- Leave to evaporate/dry
- Sand the layer lightly for the best adhesion of the next layer
- For high corrosion protection, bare metal should be treated with an anti-corrosion primer prior to the primer filler
- After use, to clean the nozzle and prevent blockage: hold the can up side down and spray until only gas is released



SUPERIOR PRIMER

WORKING CONDITIONS

- Air temperature 15°C - 30°C
- Surface temperature 15°C - 30°C but above the condensation point
- Temperature of the can 18°C - 25°C
- Relative humidity: max 80%

APPLICATION TEMPERATURE, °C

15-30

SAFETY

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Pressurized container: do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid breathing spray. Wear protective gloves/ eye protection. Use only outdoors or in a well-ventilated area.

STORAGE CONDITIONS

Cool (10°C - 20°C) and dry