

# TDS TECHNICAL DATA SHEET

# HARDENER FOR MATT CLEARCOAT

GENERAL	

CODE	DESCRIPTION
HMC05	Hardener for matt clearcoat 500ml



# DESCRIPTION

This is a special hardener, composed for mat clearcoat (MC10). Application in a ratio of 1:2 with clearcoat.

### **DEDICATED HARDENERS**

Hardener SLOW Hardener NORMAL Hardener FAST The use of the appropriate type of hardener depends on the room temperature.



The type of used hardener affects coating drying time and depends on room temperature and the preference of the painter. Proper selection of the type of hardener ensures appropriate structure and appearance of coating.

# **RULES OF CONDUCT**

Please note that after opening the container with a hardener and mixing it with clearcoat, you should immediately close it to prevent the hardening reaction in contact with air.

# STORAGE TIME AND CONDITIONS

Store in tightly closed containers, in a cool, dry place away from sources of fire and heat. Avoid exposure to sunlight. Expiration date: 6 months from date of manufacture - date on the top of container.

### **CLEANING EQUIPMENT**

For cleaning equipment can be used acrylic thinner. It is recommended to use thinner for cleaning paint spray guns.

#### HEALTH AND SAFETY REGULATIONS

See Safety Data Sheet of the product.

### **SPECIFIC WEIGHT**

About 1.0 g/cm3

PAGE 11 HARDENER FOR MATT CLEARCOAT