

TDS TECHNICAL DATA SHEET

MASKING FILM WITH INTEGRATED TAPE

GENERAL	
CODE	DESCRIPTION
MFT35	Masking film with integrated tape - 35cm x 25m
MFT60	Masking film with integrated tape - 60cm x 25m
MFT90	Masking film with integrated tape - 90cm x 25m
MFT120	Masking film with integrated tape - 120cm x 25m
MFT180	Masking film with integrated tape - 180cm x 25m
MFT260	Masking film with integrated tape - 260cm x 25m



DESCRIPTION

Gerko's transparent masking film with integrated tape is ideal for masking off car windows, walls, engine covers, etc.

PROPERTIES

- Transparent masking film with paint absorption and tape on one side
- Can be easily torn by hand
- Sticks to the surface by itself due to the static properties
- Corona treatment
- Linear cut
- 80° tape

TECHNICAL SPECIFICATIONS

Backing	Saturated crepe paper
Adhesive	Solvent-based rubber/resin adhesive
Composition	High-density polyethylene
Thickness	35 metres /8.5 microns
Corona treatment	2 sides
Density	0.957/cm3
Tolerance	Thickness: +/- 20% Width: - 15mm / + 15 mm
Tape strength	80°C (60min) 90°C (30min)

PAGE 1 | MASKING FILM WITH INTEGRATED TAPE