

TDS TECHNICAL DATA SHEET

PREMIUM CELLULOSE THINNER

GENERAL

| CODE | DESCRIPTION |
|-------|----------------------------------|
| PCT24 | Premium cellulose thinner - 24 L |



DESCRIPTION

Professional cellulose thinner for diluting cellulose paint or removing adhesive, or cleaning paint brushes and spray guns and tools. Based on aromatics and ketones.

PROPERTIES

- Cellulose thinner 100% pure
- · Professional cellulose thinner for diluting cellulose paint or removing glue
- · Dilution of paint
- · Removing glue
- Cleaning guns and tools
- · Reduces the chance of orange peel skin

NOMINAL VALUES

| NOMINAL VALUES | | |
|----------------------------|----------------------------|--|
| | | |
| Density (20°C) | 0,825 – 0,835 kg/lt | |
| Refractive index (20°C) | 1,422 – 1,428 | |
| Vapour density (air = 1) | >1 | |
| Flash point (CC) | ca18°C | |
| Auto-ignition temperature | >500°C | |
| Explosion limit | 1,0 – 13,0 %v | |
| Evaporation rate | | |
| (BUTAC = 100) | 250 (estimate) | |
| (Ether = 1) | 6 (estimate) | |
| Distillation range | | |
| IBP | 55°C | |
| DP | 115°C | |
| Solubility in water | Partially soluble in water | |
| Volatile organic compounds | 100% (830 g/lt) | |
| | | |

CHEMICAL ANALYSIS

Water: max 0,3%

PACKING

Can be obtained in bulk, drums, and cans. Other packaging is available on request.