



ZINC SPRAY

GENERAL

| CODE | DESCRIPTION |
|-------|------------------|
| AS170 | Zinc spray 500ML |



DESCRIPTION

High-quality zinc spray specially formulated to protect metal surfaces against rust and corrosion by providing a durable, long-lasting protective coating.

Perfect for automotive repairs, industrial use, and any application where reliable metal protection is required.

FEATURES

- Can be covered with paint
- Can be applied on rust
- Anti-corrosion
- Contains 90% zinc
- Heat resistant up to 300°C
- Suitable for spot welding
- Can be painted over
- Can be applied over rust
- Suitable as a welding primer

APPLICATION METHOD

1. Shake the spray can thoroughly before use.
2. Apply at a temperature between 15°C and 25°C.
3. Maintain a spray distance of 20 - 30 cm from the surface.
4. Apply 2 to 3 thin, even coats.
5. Important: Avoid applying thick layers to prevent sagging.
6. Allow approximately 3 minutes of flash-off time between coats.
7. After the final coat, allow the product to fully cure.
8. When finished, turn the can upside down and spray until only propellant comes out. This cleans the nozzle and allows safe storage of the remaining product.



DRYING TIME

Touch Dry

Depends on layer thickness, ambient temperature and humidity



ZINC SPRAY

COVERAGE

Effective Coverage

Coverage may vary based on application thickness and substrate.

STORAGE AND HANDLING

Storage

Keep in a cool, well-ventilated area, away from heat and direct sunlight. Do not expose to temperatures above 50°C.

Handling

Use only in well-ventilated environments. Always wear suitable personal protective equipment to avoid inhalation and prevent contact with skin and eyes.

SAFETY



Flammability

Flammable aerosol. Do not spray near open flame or sources of ignition.

Protective Equipment

Use gloves, eye protection, and respiratory protection when necessary.