

## SPRAY BOOTH CEILING FILTER

### GENERAL

CODE	DESCRIPTION
<b>CF50</b>	Spray booth ceiling filter 0,5m x 20m
<b>CF100</b>	Spray booth ceiling filter 1m x 20m
<b>CF150</b>	Spray booth ceiling filter 1,5m x 20m
<b>CF200</b>	Spray booth ceiling filter 2m x 20m
<b>CF</b>	Spray booth ceiling filter per m <sup>2</sup>



### DESCRIPTION

Our ceiling filter is a premium fine filter (600 g/m<sup>2</sup>) with a progressive structure, designed for professional use. With a gravimetric efficiency of 98%, it delivers highly efficient filtration. Thanks to a specific adhesive treatment applied to the synthetic fibers, the adhesive performance remains stable, even under fluctuating temperatures.

### PROPERTIES

- Manufactured from high-performance, tear-resistant synthetic fibers, constructed using gradual density technology
- Ensures uniform distribution and filtration of incoming air
- Essential component for a flawless painting process
- Filter weight per m<sup>2</sup>: 600 grams
- Efficiency EN779 – UL900: M5-M6
- Initial pressure drop: 25 Pa
- Final pressure drop: 400 Pa
- Material thickness: 25 mm
- Available customised